




LGT2654

Husqvarna's yard tractors offer premium performance with quality results. Their compact size makes them easy to maneuver and require less space for storage. Features such as fender-mounted cutting height adjustment, adjustable seat and an ergonomic steering wheel make these tractors simple and comfortable to operate. All tractors feature hydrostatic transmissions for smooth, variable forward and reverse speed. Air Induction mowing technology improves airflow within the deck, ensuring a clean, consistent cut every time. For added versatility, all models can be equipped with a range of towable accessories and mulch kit for effective lawn fertilization.



HYDROSTATIC TRANSMISSION
Easy speed and direction control with a fender mounted lever.



ELECTRIC BLADE ENGAGEMENT
Easy engagement of cutting blade/s; simply pull the switch on the control panel.



STEP-THROUGH
Ensures comfortable and easy mounting and dismounting.



FENDER-MOUNTED CUTTING HEIGHT ADJUSTMENT
Convenient fender mounted deck lever is spring assisted for easy operation.

Features

- Cruise control for comfortable operation
- Adjustable seat, while seated
- Ergonomic steering wheel
- Cast front axle for superior stability
- Air Induction; excellent cutting performance
- Anti-scalp wheels
- Deck Wash Port
- Fuel level window
- Hour meter with service minder
- Cup holder for refreshments while mowing
- Headlights for operation in dark conditions
- Bumper for protecting the front
- Collector available as accessory

Technical data

Engine manufacturer	Kohler
Power	26 hp
Cylinder displacement	747 cc
Cylinders	2
Engine cooling	Air
Generator	15 A
Battery	12 V 28 Ah
Fuel Type	Gasoline
Fuel tank volume (with reserve)	4 gal.
Fuel tank location	Rear
Engine lubrication type	Pressure with Oilfilter
Oil filter	Yes
Transmission type	Hydrostatic
Transmission manufacturer	Tuff Torq
Drive method	Lever-operated
Speed forward, min-max	0-5.2 mph
Speed reverse, min-max	0-2.9 mph
Cutting width	54 inch
Cutting deck type	Stamped
Cutting deck material	Steel
Cutting methods	Collect/Mulch/Side ejection
Cutting height, min-max (approximate)	1.5 - 4 inch
Cutting height adjustment	Notch
Cutting height steps	7
Cutting height adjuster	Fender-mounted
Blade engagement	Electric clutch
Blades	3
Blade type	Hi Performance
Anti-scalp wheels	4
Nose roller	Yes
Powder-coated cutting deck	Yes
Belt tension release	Yes
Greasable mandrels	Yes
Deck Wash Port	Yes
Seat back height	High
Seat material	Vinyl
Steering wheel type	Deluxe Overmolded
Front-End Protection	Tube Bumper
Hour meter	Digital with pre-programmed service intervals
Collector	Available as accessory
BioClip® kit/plate	Available as accessory
Tire size, front	16x6.5-8"
Tire size, rear	22x9.5-12"
Turning radius, min	18"
Wheelbase	48"
Base machine, length	70.5 inch
Base machine, width (chute down)	67.5 inch
Base machine, width (chute up)	57 inch
Base machine, height	42.5 inch
Weight	550 lbs
Homeowner Warranty	3 Year Limited / 5 Year Limited Chassis and Axle / 10 Year Limited Deck Shell

ARTICLES		
960 43 01-83	LGT2654	\$ 2,399.95

